



## TECHNICAL DATA SHEET

## ACRYLIC THINNER

Special mixture of organic solvents used for diluting acrylic paints/varnishes, polyurethane varnishes and basecoats.

### USAGE

- Basecoats with metallic, pearl and non-metallic effect
- Polyurethane varnish
- Acrylic paints/varnishes

### PHYSICAL PROPERTIES

CODE	DESCRIPTION	PIECES PER PALLET
AV01	Acrylic thinner 1 liter	576
AV05	Acrylic thinner 5 liter	160
AV25	Acrylic thinner 25 liter	24
Comments	Adjusting time of evaporation of solvents from sprayed varnish, depending on the temperature conditions, is essential for the proper appearance of the surface. Sprayed mixture between the gun nozzle and painted surface cannot lose diluents by evaporation. It's too rapid evaporation causes so-called „dusting” of and does not allow to reach full glow and proper flow.	

### APPLICATION CONDITIONS

Ready for use. Adjusting the viscosity of mixture depends on the ambient temperature and the density of the varnish.

### RULES OF CONDUCT WHEN APPLYING

Universal thinner pour directly to prepared varnish.

### STORAGE TIME AND CONDITIONS

Store in tightly closed containers, in a cool, dry place away from sources of fire and heat. Avoid exposure to sunlight. Expiration date: 24 months from date of manufacture - date on the top of container.

### HEALTH AND SAFETY REGULATIONS

See Safety Data Sheet of the product.

### SPECIFIC WEIGHT

About 0.9 g/cm<sup>3</sup>