

AZURE MASKING TAPE

Gerko azure high temperature masking tape characterized by a flexible crepe paper backing and a solvent borne rubber resin adhesive. Designed for spray-painting operation in car repair with temperature resistance up to 110°C. Special colour backing improves visibility during the paint and masking process. Easy removal, thanks to the conformable paper, from curved moldings.

APPLICATION CONDITIONS

Professional masking for spray painting in Automotive refinishing industry
Indoor professional masking and painting operations

PROPERTIES

- Strong adhesion
- Excellent holding power
- Excellent conformability on curved profiles
- Easy to remove without adhesive transfer
- High visibility
- Suitable for IR and UV curing
- 3 days UV resistance
- Premium quality

PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOR	PIECES PER BOX	BOXES PER PALLET
MAT18	Azure Masking Tape 18 mm x 50 m	Blue	48	120
MAT24	Azure Masking Tape 24 mm x 50 m	Blue	36	120
MAT30	Azure Masking Tape 30 mm x 50 m	Blue	32	120
MAT36	Azure Masking Tape 36 mm x 50 m	Blue	24	120
MAT48	Azure Masking Tape 48 mm x 50 m	Blue	24	90

GERKO

PAINT RELATED PRODUCTS



TECHNICAL DATA SHEET

AZURE MASKING TAPE

NOMINAL VALUES

	VALUE
Backing	Saturated crepe paper
Adhesive	Natural rubber and solvent-based resin
Tensile Strength MD	36 N/cm
Elongation at Break MD	9 %
Peel Adhesion on Stainless Steel Paper thickness	2.3 N/cm
Paper thickness	130 µm
Total weight	93 g/m ²
Temperature resistance	110°C - 30 min