



TECHNICAL DATA SHEET

BRUSHABLE SEAM SEALER

Gerko brushable seam sealer is a one-component product based on synthetic rubber that hardens by evaporation of solvents. It is designed for sealing welded joints, pressure welds and metal soldered joints. It forms a durable and elastic seal that ensures resistance to water, petrol, oils and high temperatures (to 60°C).

It can be painted on steel (untreated or primed metal sheets, painted steel sheets, steel, galvanized steel), aluminium, primer paints and paint coatings with all lacquer systems (fresh or after hardening).

PROPERTIES

- Very easy to brush
- Pulls no wires
- Displays original structure
- Very strong adhesion

PHYSICAL PROPERTIES

CODE	DESCRIPTION	FORMAT	PIECES PER PALLET
BSS010	Brushable seam sealer 1 kg	1 KG	600

SUBSTRATE PREPARATION

The surface must be clean (remove all corrosion centres), degreased and dry thoroughly.

APPLICATION CONDITIONS

Apply the product on a clean surface with a hard brush. The seam sealant shows no dripping tendency during application. The optimum temperature of application: from 10°C to 25°C.

DRYING TIME

- Coating surface dryness – 20 - 30 minutes at 20°C.
- Hardening time – 1 mm thick layer daily.
- The surface can be painted “wet on wet” or after hardening with all lacquer systems.
- The thickness of applied layers has a considerable effect on the drying time.

CHEMICAL PROPERTIES

This is a grey paste with an aromatic, sweet odour, containing toluene and butyl acetate. The maximum content of VOC for ready to use product is 540 g/l.

STORAGE

Store the product tightly closed in original container, in dry and cool places, away from fire and heat sources at temperatures from 5°C to 20°C. Do not expose to direct sunlight.

GUARANTEE PERIOD

12 months from the date of manufacture.

HEALTH & SAFETY RECOMMENDATIONS

Product safety data sheet and applicable health and safety regulations for working with chemical agents.