



TECHNICAL DATA SHEET

CABINE COATING PRO

Gerko cabine coating pro is a temporary transparant, tacky and washable coating for the protection of spraybooth walls against overspray.

PROPERTIES

- Cabine coating pro is a clear aqueous coating for protection against overspray in spraybooths
- It can be applied to walls, windows and light armatures
- The sticky properties contribute to a dust free surrounding, because airborne particles will be collected and hold
- After 2 - 8 weeks, depending on the amount of contamination, the tacky coating can be easily removed with warm water
- Biodegradable and silicone free
- Temperature resistant: 65°C

PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIECES PER BOX	PIECES PER PALLET
CCP05	Cabine coating pro 5L	Transparant	1	96
CCP25	Cabine coating pro 25L	Transparant	1	24

SAFETY

Wear a suitable safety-mask during spraying. Consult MSDS for details.

APPLICATION

NOTE: new or recently painted walls usually have a surface-tension, which can cause an improper result. It is recommended to clean the surfaces with Gerko waterbased degreaser WD05 and grey scotch brite SB02. Application by roller is possible, however best result is obtained by spraying. Cabine coating pro is simple to apply by sprayun (2.0 mm) or airlesspump. Apply a thick layer. 4 m²/ltr. Slightly warm up spraybooth after application.

REMOVAL

The contaminated coating is easy removable with water. Using warm water will facilitate the removal (a hot water pressure washer is preferred). Don't dispose in public sewerage.