



TECHNICAL DATA SHEET

CLEARCOAT 1K

Gerko Clear Coat 1K is a high performance 1K lacquer which gives a crystal clear finish that can be applied over all water and solvent based basecoats. The surface gets a protective layer and a completely new look. Ideal for smart repairs.

PROPERTIES

- Ultra gloss finish with excellent gloss retention
- Superior build
- Ideal distance to object is 25 cm
- Apply 2 full layers with a flash-off time of 10 min for a good result
- UV and petrol resistant 1K lacquer
- Fast drying 1K lacquer

PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIECES PER BOX	PIECES PER PALLET
AS300	Clearcoat 1K 500 ml	Transparent	12	1200

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 15 min. Tack free ca 30 min. Dry ca. 2 hours.

DIRECTIONS BEFORE USE

- Use at room temperature
- Shake before use
- Surface must be dry and clean, free from dirt, rust, grease etc.
- Spray crosswise thin layers on the object or surface to be coated
- Leave to evaporate/dry
- After use, to clean the nozzle and prevent blockage: hold the can up side down and spray until only gas is released

WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.

STORAGE CONDITIONS

Cool (10°C - 20°C) and dry