

TECHNICAL DATA SHEET

DUCT TAPE

Gerko duct tape has been specially developed to protect vehicle parts during sanding and blasting work. Also useful when transporting a damaged vehicle.

PROPERTIES

- Excellent adhesion properties at low & high temperatures
- Good performance on rough surface
- Excellent tearing & unwinding
- Clean removal for long period
- Free from silicone
- Easy to tear off in both length and width
- Can be applied to plastic parts, spoilers, bumper strips, mirrors, but also sheet metal

PHYSICAL PROPERTIES

| CODE | DESCRIPTION | COLOR | PIECES PER BOX | BOXES PER PALLET |
|-------|----------------------|--------|----------------|------------------|
| CTZ50 | Duct tape 50mm x 50m | Black | 18 | 720 |
| CTG50 | Duct tape 50mm x 50m | Silver | 18 | 720 |

NOMINAL VALUES

| | VALUE |
|-----------------------------------|---------------------------|
| Carrier material | Laminated linen |
| Width | 50mm |
| Length | 50m |
| Thickness | 0.30mm |
| Mesh | 70 mesh |
| Tensile strength | 44 N/cm |
| Stretch | 9% |
| Adhesive strength on steel N/25mm | 18 |
| Temperature resistance | 60°C |
| Packing | Per roll in a plastic bag |
| Packing unit | 18 rolls in a box |