

TECHNICAL DATA SHEET

# **FOAM MASKING TAPE**

Gerko foam masking tape is the product to use for masking gaps between bonnets, doors and car body parts. It protects the joint perfectly, absorbs the paint and avoids edge building.

## PROPERTIES

- The foam allows an easy cutting to desired length and size and ensures a proper isolation
- The adhesive ensures a successful use without leaving any residue once used

#### PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIÈCES PAR PALLET
FT13	Foam masking tape 13mm x 50m	White	120
FT19	Foam masking tape 19mm x 50m	White	120

### NOMINAL VALUES

	VALEURS
Width	13mm or 19mm
Length	50m or 35m
Temperature resistance	100°C
Adhesive	Rubber
Density	30kg/m <sup>3</sup>
Peel Adhesion N/25mm	6
UV Resistance	Limited

## CONDITIONS DE STOCKAGE

It is advisable to store the product in areas with temperatures below 35°C and normal ventilation. Avoid keeping the product stored for more than twelve months. Make a good rotation of stock for an optimal result.

Gerko International | Beemdenstraat 36, 2340 Beerse | Belgium T. +32 3 312 21 30 | info@gerkoproducts.com | www.gerkoproducts.com