



## TECHNICAL DATA SHEET

## MASKING FILM

Gerko HDPE masking film is perfect for quick and efficient covering of a vehicle and protects it against overspray, dirt and dust.

### PROPERTIES

- Translucent HDPE masking film to protect from overspray, dirt and dust
- Corona treated with Gerko logo on the paintable side
- Easy to use by one man
- Strong and elastic performance Easy to cut
- Static properties, clings to the object surface
- Per roll in a carton box
- Can be used with infrared drying
- Thickness: 10 µm

### PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIECES PER BOX	PIECES PER PALLET
PM4015	Masking Film 4m x 150m	Transparent	1	112
PM40	Masking Film 4m x 150m	Transparent	1	84
PM48	Masking Film 4m x 150m	Transparent	1	60
PM50	Masking Film 4m x 150m	Transparent	1	135
PM60	Masking Film 4m x 150m	Transparent	1	112

### PRODUCT INFORMATION

FORM	MATERIAL	ROLL WIDTH	TEMPERATURE RESISTANCE	WATER SOLUBLE
Film on a roll	HDPE	95cm	120°C	No

### TECHNICAL PROPERTIES

- Paint adhesive
- High static power
- High tensile strength
- IR drying by max 120°C

### STORAGE

+ 20°C/± 10°C, in an enclosed space with a relative humidity of 30-90% without exposure to UV

### SHELF LIFE

12 months from delivery date