



TECHNICAL DATA SHEET

PLASTIC PRIMER

Gerko Plastic Primer is a professional adhesion promoter for all common plastics. The product will ensure with its unique composition a great improved adhesion to operations such as plastic repair, gluing and painting. Gerko plastic primer will give a better adhesion on difficult surfaces. It has a very fast drying, only after 10 minutes you can start the next operation.

PROPERTIES

- Universally applicable
- Effective adhesion promotor
- Fast drying
- Can be painted over after just 10 minutes
- Excellent to build up your repair

PHYSICAL PROPERTIES

| CODE | DESCRIPTION | COLOUR | PIECES PER BOX | PIECES PER PALLET |
|-------|-----------------------|-------------|----------------|-------------------|
| AS050 | Plastic Primer 400 ml | Transparent | 12 | 1200 |

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 10 min. Over paintable after ca. 30 min.

DIRECTIONS BEFORE USE

- Use on room temperature
- Shake before use
- Surface must be dry and clean, free from dirt, rust, grease etc.
- Preferably the surface should be sanded lightly
- Spray thin cross wise layers
- Leave to evaporate/dry
- After use, to clean the nozzle and prevent blockage: hold the can up side down and spray until only gas is released

WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

APPLICATION TEMPERATURE, °C

- 15 - 30

STORAGE CONDITIONS

Cool (10°C - 20°C) and dry

SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.