



TECHNICAL DATA SHEET

SEMI GLOSS BLACK

Gerko high gloss black is a decorative paint for any type of bodywork. Suitable for the individual decoration of cars and motorcycles. Ideal as contrast paint and for partial paintwork.

PROPERTIES

- Fast drying
- Excellent adhesion on many surfaces and materials
- Exceptional hiding power
- Smooth finish
- Resistant to chemicals and weather conditions

PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIECES PER BOX	PIECES PER PALLET
AS090	Semi gloss black 500 ml	Black	12	1200

DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 20 min. Dry to touch 40 min. Over paintable: after 60 min.

DIRECTIONS BEFORE USE

- Use on room temperature
- Shake thoroughly before use; at least 2 min after the shaking ball has come loose
- Surface must be dry and clean, free from dirt, rust, grease etc.
- When sprayed on bare metals or plastics a suitable primer is advisable
- Spray thin crosswise layers on the object or surface to be coated
- Leave to evaporate/dry
- After use, to clean the nozzle and prevent blockage: hold the can up side down and spray until only gas is released

WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

APPLICATION TEMPERATURE, °C

- 15 - 30

STORAGE CONDITIONS

Cool (10°C - 20°C) and dry

SAFETY

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves/ eye protection. Use only outdoors or in a well-ventilated area.