



## TECHNICAL DATA SHEET

# WHEEL SPRAY

Gerko Wheel Spray is a glossy silver coloured spray paint perfect to repair rims very fast and easy.

### PROPERTIES

- Very fast drying, good adhesion
- Glossy, good flexibility, good hardness
- Excellent UV protection
- Good outdoor durability
- Non yellowing

### PHYSICAL PROPERTIES

CODE	DESCRIPTION	COLOUR	PIECES PER BOX	PIECES PER PALLET
AS130	Wheel Spray 400 ml	Light silver	12	1200

### DRYING TIMES

Depends on layer thickness, temperature and ventilation. Indication: dust dry ca. 30 min. Sandable ca. 5 hours. Over-paintable (with same product) after ca. 30 min.

### DIRECTIONS BEFORE USE

- Make sure that the surface is dry clean and free of oil, grease ect. Preferably the surface should be sanded lightly
- Spray with a distance of about 15 cm, cross wise, several layers until a smooth surface is formed
- Let it dry
- Sand the layer lightly for the best adhesion of the next layer

### WORKING CONDITIONS

- Air temperature 15°C - 30°C
- Surface temperature 15°C - 30°C but above the condensation point
- Temperature of the can 18°C - 25°C
- Relative humidity: max 80%

### RECOMMENDATIONS

- When used in combination with (unknown) primers, the compatibility and adhesion should be tested first
- For safety, health and to promote the drying, this product should only be use in well ventilated areas